Flush Door



WINDOWS - DOORS - CONSERVATORIES

Market leading design

Secured by Design & Part Q as standard

2 low threshold options

Coloured substrate

Unique rebate system

Open out

84mm outerframe - bespoke rebate adaptor

Benefits

Suited to our Flush casement range

High security performance and peace of mind

Versatile design to suit any application

Improved aesthetics when Sashes are opened

Smaller Sash width with increased adjustment

Suites external flush appearance

Extra weathering whilst maintaining flush appearance

Specification

Colour Options

Signature White

Foils

- Standard Anthracite on white, golden oak and rosewood
- Special Agate grey, anthracite grey, anthracite grey smooth, black/brown, chartwell green, cream, irish oak & light grey. Bevelled is only available in smooth slate grey and smooth anthracite grey
- Bespoke Any other combination or dual foil

Hardware

- Shootbolt locking on all doors
- 4 3 Hook locking on Master Sash
- All Hardware tested to Secured by Design standards
- All gearing is concealed

Handles

- < Black
- < White
- < Gold
- Chrome

Hinge Finishes

- Black as standard
- White option available

Sills

Energy Performance & U Values

Unit Size	DER	U Value
28mm	В	1.4
36mm	Α	1.2

Options

- Aluminium Rebated Threshold options
- Yale 3 star anti-snap cylinder

Single Door - Width Sizes

Min. Width	Max. Width
615mm	1215mm

Double Door - Width Sizes

Min. Width	Max. Width
1125mm	2325mm

Single & Double Door - Height Sizes*

Min. Height	Max. Height
1740mm	2450mm

^{*} PVC Threshold

